



MATERIAL SAFETY DATA SHEET

MSDS 0218

Section 1 -- PRODUCT AND COMPANY IDENTIFICATION

Product: Metacaulk Wrap Strip

HMIS CODES:

Health:	1
Flammability:	0
Reactivity:	0
PPI:	B

PRODUCT CODES:

- 66135
- 66136

CHEMICAL FAMILY:

Organic/Inorganic

USE:

Firestopping Material

MANUFACTURER'S NAME:

The RectorSeal Corporation
2601 Spenwick Drive
Houston, Texas 77055 USA

DATE OF PREPARATION:

August 27, 2004
Chemtrec 24 Hours
(800) 424-9300

TECHNICAL SERVICE TELEPHONE NO.

(800) 231-3345

Section 2 -- COMPOSITION/INFORMATION ON INGREDIENTS

% by Weight CAS No. Ingredients Units

None as defined by OSHA Hazard Communication Standard 29 CFR 1910.1200.

Section 3 -- HAZARDS IDENTIFICATION

SUMMARY OF ACUTE HAZARDS:

May cause skin irritation.

ROUTE OF EXPOSURE, SIGNS AND SYMPTOMS

INHALATION:

Not a respiratory irritant.

EYE CONTACT:

Contact may cause eye irritation.

SKIN CONTACT:

Contact may cause skin irritation.

INGESTION:

Possible irritation to mucous membranes of the mouth, throat, and stomach.

SUMMARY OF CHRONIC HAZARDS:

None known.

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE:

Persons with pre-existing skin conditions or chemical allergies may be more susceptible to contact effects of the cured elastomer.

Section 4 -- FIRST AID MEASURES

INHALED:

Not a respiratory irritant.

SKIN:

Wash with soap and water. If irritation occurs, seek medical attention.

EYES:

Immediately flush with large amounts of water. If irritation occurs, seek medical attention.

SWALLOWED:

If swallowed, call a physician immediately. Only induce vomiting at the instruction of a physician. Never give anything by mouth to an unconscious person.

Section 5 -- FIRE FIGHTING MEASURES

FLASH POINT	LEL	UEL
-------------	-----	-----

None	N/D	N/D
------	-----	-----

EXTINGUISHING MEDIA

Foam, dry chemical, carbon dioxide or water fog.

SPECIAL FIRE FIGHTING PROCEDURES:

Wear self-contained breathing apparatus (SCBA) and other protective clothing.

UNUSUAL FIRE AND EXPLOSION HAZARDS:

Fire conditions will activate product causing intumescence to occur.

Section 6 -- ACCIDENTAL RELEASE MEASURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:

Pick up debris to prevent footing hazard.

Section 7 -- HANDLING AND STORAGE

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING:

Do not store near heat, sparks, or open flames.

OTHER PRECAUTIONS: KEEP OUT OF REACH OF CHILDREN.

Section 8 -- EXPOSURE CONTROLS/PERSONAL PROTECTION

RESPIRATORY PROTECTION (SPECIFY TYPE):

None required.

VENTILATION - LOCAL EXHAUST:

N/A

SPECIAL:

N/A

MECHANICAL (GENERAL):

N/A

OTHER:

N/A

PROTECTIVE GLOVES:

None required.

EYE PROTECTION:

None required.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT:

None required.

WORK/HYGIENIC PRACTICES:

Where use can result in skin contact, wash exposed areas thoroughly before eating, drinking, smoking, or leaving work area. Launder contaminated clothing before reuse.

Section 9 -- PHYSICAL AND CHEMICAL PROPERTIES

BOILING POINT:	N/A
SPECIFIC GRAVITY (H ₂ O = 1):	1.63
VAPOR PRESSURE (mm Hg):	N/A
MELTING POINT:	N/A
VAPOR DENSITY (AIR = 1):	N/A
EVAPORATION RATE (ETHYL ACETATE = 1):	N/A
APPEARANCE/ODOR:	Black / Mild Odor
SOLUBILITY IN WATER:	Insoluble

Section 10 -- STABILITY AND REACTIVITY

Section 15 -- REGULATORY INFORMATION

REGULATORY DATA

Ingredient Name:

None

SARA 313 N/A

TSCA Inventory All components listed

CERCLA RQ N/A

RCRA Code N/A

Section 16 -- OTHER INFORMATION

This document is prepared pursuant to the OSHA Hazard Communication Standard (29 CFR 1910.1200). The information herein is given in good faith, but no warranty, expressed or implied is made. Consult RectorSeal for further information: (713) 263-8001

© 2005-2007 | <http://www.blazeframe.com> | All Rights Reserved |